

**Sleek, modern integrated system  
— for Venetian, Pleated and Cellular blinds**



**no holes, no screws, just style**

INTU<sup>®</sup> is a versatile and easy-to-install blind system designed to fully integrate with most window systems, including tilt and turn windows and glazed doors.

Suitable as a Venetian, Pleated and Cellular blind, the sleek profile fits perfectly into the bead of most modern window and conservatory systems. This conceals the mechanism and fixing brackets while allowing complete control of light and heat. With no free-hanging cord loop, INTU<sup>®</sup> is one of the safest blinds available.

A wide range of colour options are available in both venetian (16 or 25mm) or Pleated 20mm and Cellular (honeycomb) fabrics. INTU<sup>®</sup> offers additional sales opportunities, when combined with the energy efficiency of Pleated and Cellular fabric.

# INTU® Beadfit Venetian

**Headrail:** sits flush with window, inside frame, close to glass.

**Top Control:** adjust slat angle with slider. For blinds installed out-of-reach, slider can be operated using optional 300 or 600mm rod.

**Venetian Slat:** available in 16 and 25mm widths and a large range on colours.

**Venetian Bottomrail:** lip profile reduces light gap and provides 'grab' area for hand raise/lower operation.

**End Caps:** colour coordinated to improve appearance while acting as tension cord guide.


**Top Corner Fixing Bracket:** anchors between bead rubber seal and glass, providing a secure fixing for the headrail.

**Side Profiles:** held in position by retaining brackets. Available in 4 shapes to suit most window styles.


**Tension Cord:** maintains profile of the blind; eliminates any 'rattle' against glass.

**Bottom Corner Bracket:** anchors between bead rubber seal and glass, providing a secure fixing for the tension cord.


## options –



**Pleated fabric**



**Pleated Multizone**



**Cellular fabric**

## Sizes

Suits 95% of popular window sizes

Bead depth	Min. 11mm
	Max. 27mm
Blind width	Min. 240mm
	Max. 1400mm
Blind drop	Max. 2000mm
Blind surface area	Max. 1.5 sq m

## Installation

'Installation Survey Guide' provides full instructions.  
No drilling or fixing screws for brackets.  
Blinds supplied pre-tensioned ready to fit.  
Bracket fixing tool supplied with every order.

## Colour Guide

Rail and external components — white, silver & brown.  
Internal components — white.  
Slat and fabric — as per standard programme.  
Cord and ladder cord — co-ordinating range.

## Support Material

Demo kit with glass — various  
Multiproduct page — MSM4239  
Slat selector — MSV4233  
Retail brochure — MSM4240  
Installation survey guide — MSM4242  
Fitting instructions — MSM4236  
Fax back order form — MSP4744/MSV4236  
Trade price list — part code not applicable.